

you can  
**Canon**

**iPF810 / iPF820**  
Large Format  
Print Solutions

Designed for high volume  
CAD & GIS printing

iPF810 / iPF820

For fast, high quality production CAD & GIS work the imagePROGRAF iPF810 and iPF820 are ideal. Designed for high volume printing in busy print for pay and large corporate CAD & GIS environments, these 44" large format printers deliver non-stop, high quality results at blistering speeds.

Accurate line reproduction with a range accuracy of  $\pm 0.1\%$  and a minimum line width of 0.02mm

Dual roll to handle large print runs with different types and sizes of media (iPF820).

Incredibly fast with A1 prints in just 24 seconds and A0 in 47 seconds (draft mode).



Superb graphics with vivid colours and solid image consistency

Continuous productivity with high capacity 330ml and 700ml "hot swap" ink tanks - replaceable during production.

Economy printing mode for lower running costs.



iPF810

*We Speak Image*

<b>44</b> inch	<b>2,400</b> x <b>1,200dpi</b>	<b>4</b> pl	<b>5</b> colours	<b>A1</b> 24 seconds	<b>A0</b> 47 seconds	15,360 nozzles	HP GL/2 & HP RTL Compatible	80Gb HDD
-------------------	--------------------------------------	-------------	---------------------	-------------------------	-------------------------	-------------------	-----------------------------------	-------------

- Single roll with an optional take-up unit for consecutive printing on large print jobs (iPF810).
- HPGL/2 and HP RTL compatibility and includes HDI Driver for CAD applications as standard.
- Large LCD with graphics ensures easy operation.
- Nesting and auto rotation to minimise paper wastage.
- Borderless printing for maximum impact and to save time on finishing.

Class Ink Type	44-inch Pigment and Dye reactive ink, 5 colours (MBK, BK, C, M, Y)
Maximum Print Resolution	2,400 x 1,200 dpi
Printing Speed Plain paper (Full Colour CAD Drawing)	Economy Mode – A0: 0.47, A1: 0.24
Dimensions, Weight (Net) W x D x H (mm), (kg)	Draft Mode – A0: 0.47, A1: 0.24 Standard Mode – A0: 1.16, A1: 0.38 High Quality Mode – A0: 3.10, A1: 1.35
Dimensions, Weight (Packaged) W x D x H (mm), (kg)	iPF810: Main Unit with Printer Stand and Basket 1,893 (W) x 975 (D) x 1,144 (H) mm; Weight: approx. 141 kg iPF820: Main unit with printer stand, lower paper roll and basket: 1,893 (W) x 1,291 (D), 1,144 (H); Weight approx: 189 kg
Power Supply Input power	AC 100 - 240 V (50/60 Hz)
Power consumption Standby power consumption (At the low power mode)	190 W or less
Operational Environment Acoustic Noise Acoustic pressure Acoustic power Minimal Line Width Line Accuracy	6 W or less (when IEEE1394 is mounted, 11 W or less) 5 W or less (when IEEE1394 is mounted, 10 W or less) 1 W or less (In compliance with Executive Order of the President of the United States of America) Temperature: 15 - 30°C, Humidity: 10 - 80% (Condensation free)
Operation Panel Display Language on operation panel Displayable Language on LCD	Operation: 52 dB (A) or less, Standby: 35 dB (A) or less Operation: 6.8 Bels or less 0.02mm (Theoretical value) ±0.1 % or less (User adjustments necessary. Printing environment media must match that used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only.) Large LCD: 160 x 128 dots, Key x 12, LED x 5 US-English, Japanese US-English, French, German, Italian, Spanish, Chinese (simplified), Korean, Japanese (Kanji), Russian GARO, HP-GL/2, HP RTL
Printer Language Interface USB2.0 Hi-Speed Type Mode Connector type Ethernet Type Standard	Built-in Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Series B (4 pins)
Protocol	Built-in IEEE 802.3 10base-T IEEE 802.3u 100base-TX / Auto-Negotiation IEEE 802.3 x Full Duplex IPX/SPX (Netware 4.2(J), 5.1(J), 6.0(J)) SNMP (Canon-MIB), HTTP, TCP/IP, AppleTalk
IEEE1394 Type Standard Data-transfer time Connector type Operating Systems supported Regulations	Slot card type IEEE1394 - 1995, P1394a, Half duplex, Data/Strb differential serial 100 / 200 / 400 Mbit/sec. In compliance with IEEE1394 - 1995, 6 pins, No power supply Windows 2000, XP, Server 2003, Vista / Macintosh OS 9, OS X CE Mark, CB Certification, TUV (GS), Gost-R, UL, FCC class B
<b>HARD DISK DRIVE</b> Capacity	80 GB
<b>MEMORY</b> Standard Memory	384 Mb
<b>PRINT HEAD</b> Model Type Head configuration Nozzle pitch Nozzle per chip Droplet size	PF-03 Bubble-jet on demand 6 colours integrated type (6 chips per print head) 1,200 dpi x 2 MBK: 5,120 nozzles, Other Colours: 2,560 nozzles each 4 pl per colour

Ink Tank Model	PFI-303: BK, MBK, C, M, Y (330 ml) PFI-703: BK, MBK, C, M, Y (700 ml)
Media Handling Roll paper	iPF810: 1 Roll, Front-loading, Front Output, iPF820: 2 Rolls, Front Loading, Front Output
Cut sheet Paper path switch	Front-loading, Front Output (Manual feed using media locking lever) iPF820: Auto-changover (upper/lower roll), iPF810: Manually switchable by user
Media type Roll paper	Standard Paper 80 gsm, Standard Paper 90 gsm, Matt Coated Paper 90 gsm, Glossy Photo Quality Paper 190 gsm / 240 gsm / 300 gsm, Satin Photo Quality Paper 190 gsm / 240 gsm / 300 gsm, Photo Realistic Paper 210 gsm, Pearl Photo Paper 260 gsm, Matt Coated Paper 120 gsm / 140 gsm / 180 gsm, Opaque White Paper 120 gsm, High Resolution Self-adhesive Graphic Paper 140 gsm, High Resolution Barrier Paper 180 gsm, Glossy Proofing Paper 195 gsm, Semi-Glossy Proofing Paper 195 gsm / 255 gsm.
Media Size Roll paper (width)	ISO: A3, A2, A1, A0, JIS: B2, B1, B0, ARCH: 24", 30", 36" Others: 10", 14", 16", 17", 42", 44"
Cut sheet	ISO: A4, A3, A3+, A2, A2+, A1, A0, B4, B3, B2, B1, B0, DIN: C4, C3, C2, C1, C0 JIS: B4, B3, B2, B1, B0 ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34", 28 x 40", 34 x 44" ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36", 26 x 38", 27 x 39", 30 x 42", 36 x 48" Photo: 20 x 24", 18 x 22", 14 x 17", 10 x 12", 10 x 15", 8 x 10", 12 x 16", 16 x 20" (US Photo size) Poster: 20 x 30", 30 x 40", 42 x 60", 44 x 62", 300 x 900 mm Roll paper & Cut sheet: 0.07 - 0.8 mm
Media Thickness Maximum Outside Diameter of Roll Paper Media Core Size Media Width	150.0 mm Internal diameter of roll core: 2" / 3"
Minimal Printable Paper Length Maximum Printable Paper Length	Roll paper: 254 - 1118 mm, Cut sheet: 203 - 1118 mm 203 mm
Margins (Top, Bottom, Sides) Recommended area	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m
Printable area	Roll paper: Top: 20 mm, Bottom: 5 mm, Side: 5 mm Cut sheet: Top: 20 mm, Bottom: 23 mm, Side: 5 mm
Media width for borderless printing	Roll paper (borderless print): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 23 mm, Side: 3 mm
<b>OPTION</b> Media Take-up Unit (iPF810 only) Portable Media Basket (iPF810 only) Roll Holder Set (2-inch core spindle with 3-inch media tube attachment and borderless printing space) IEEE1394 Expansion Board	TU-06 BU-03 RH2-44 EB-05
<b>CONSUMABLES</b> Ink Tank Print Head Maintenance Cartridge	PFI-303: BK, MBK, C, M, Y (330 ml) PFI-703: BK, MBK, C, M, Y (700 ml) PF-03 MC-09

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.  
www.canon.com

Canon Europa N.V.  
www.canon-europe.com

English-UK Edition 0127W496 -  
5026173428682  
© Canon Europa N.V., 2008 (0908)

Canon (UK) Ltd  
Woodhatch, Reigate  
Surrey RH2 8BF  
Telephone No: 01737 220000  
Facsimile No: 01737 220022  
www.canon.co.uk

Canon Ireland  
Arena Road, Sandyford Industrial Estate  
Dublin 18, Ireland  
Telephone No: 01-2052400  
Facsimile No: 01-2958141  
www.canon.ie

